



CONTINEST®

Space to go



Tailored to meet the highest expectations **Container Kitchen**

Combining high-quality kitchen technology equipment in the container kitchen, the ideal design with fresh and high-quality food can provide true culinary experiences for the guests



Have a bite of our newest product!

Container Kitchen

The Container Kitchen is a mobile, modular and exceptional kitchen technology solution; the technical design and production of which takes into account specific gastronomic and kitchen technology needs, as well as sustainability aspects.

With the newly developed modular kitchen container, we offer our customers quality kitchen models and premium solutions, with which technological requirements and **the desired professional brand image can be flexibly shaped and customized to fit** the ideal location and gastronomic concept.

A container kitchen developed according to the customer's needs **can be installed quickly and easily and provides** an ideal solution for any event or project requiring temporary infrastructure.

The professional background of Container Kitchen is qualified by two Hungarian-owned companies: **Continest, which develops and manufactures** foldable container technology, and **Skill Trade Kitchen Technology, which designs and develops** industrial kitchen technology solutions.

Our partner: **skilltrade**



Areas of use



Restaurant industry, hotel industry, tourism



Catering



Healthcare and defence industry



Event industry (i.e., sporting events, festivals)



Institutions



Urban, industrial and residential areas

Why is Container Kitchen the best choice?

- modular and mobile
- complies with international ISO standards or with metric dimensions (3×6 m or 3×12 m)
- cost-effective design
- fast project time and delivery
- sophisticated, brandable design



Standard equipment

- 20' or 40' container
- frame: steel structure
- walls: sandwich panel, polyurethane foam filling (60 mm), galvanized or stainless-steel inner lining
- electrical equipment: external connectors, distribution panel with automatic breakers, fuses, sockets, 2 pcs 36W lamps, air conditioning if requested
- outer covering: sintered, wood or stone
- floor: standard or waterproof design
- doors and windows: lockable, standard design, openable service window




Dimensions and functions






- 20' or 40' kitchen box
- 20' or 40' café box
- 20' or 40' canteen box
- 20' or 40' canteen PRO
- 20' or 40' event PRO




The professional background of Container Kitchen is qualified by two Hungarian-owned companies: **Continest**, which develops and manufactures foldable container technology, and **Skill Trade Kitchen Technology**, which designs and develops industrial kitchen technology solutions.

Mnfr.	Image	Description	Model	Voltage (V)	Size (mm)	Power (kW)	Weight (KG)
YD		400-liter upright single door refrigerator with static cooling stainless steel inside and out, roof aggregate, auto defrosting and condensate drainage, temperature control with electronic thermostat, 1 lockable RM door, adjustable legs Refrigerant R600a. cooling: -5°C/+5°C, up to +38°C outside temperature	YBL9313GR	230	600x700x1950		95
YD		400-liter upright single door freezer with ventilated cooling (-), stainless steel inside and out, rounded inner corners, roof aggregate, auto defrosting and condensate drainage, temperature control with electronic thermostat, solid RM door with reversible hinges, adjustable legs Refrigerant R290. cooling: -22°C/-17°C, up to +38°C outside temperature With 3x 530x480 mm sintered grid shelves	YBF9207GR	230	600x740x1950	0,50	75
Inoxid		Double basin sink, 500 × 600 × 300 mm basins Stainless steel (AISI 304) design, reinforced lower legs, tap hole, adjustable legs. Backsplash: 100×20 mm	2M5060 120-70		1200×700×900		
Inoxid		Grease trap Stainless steel design, adjustable legs, size 50 stubs.					
Stefinox		Mini Pre-rinse faucet with two-button tap and spout TOP-CLASS Separate faucet at basin level, large-handled grip, detachable rinse head, continuous spray option, reinforced connections to prevent leaks, country of origin: Italy.	RUB00958508		magasság: 600 mm		
Inoxid		Adjustable wall shelf, perforated Made of stainless steel, height-adjustable with wall rails and brackets, multi-level options as desired, shelves are perforated with raised back edges Material: K033, ASIS304	Á F P 40-120		1200×400		
Forcar		Worktop Refrigerator with 2 doors, back-splash, and cooling unit Lower compartment GN 1/1 compatible, ventilation cooling, digital controls, door access, stainless steel design (AISI 304), rounded interior, 60 mm thick thermal insulation (CFC/HCFC free), magnetic door sealing rubbers, automatic defrosting and condensate evaporation. Basic accessories: 1pc GN 1/1 sintered grid shelf and pair of rails / door. Cooling range: -2/+8°C Energy classification: B Max ambient temperature/humidity: +32°C / 55% Refrigerant: R600a	G-GN2200TN	230	1360×700×860	0,2	116

Mnfr.	Image	Description	Model	Voltage (V)	Size (mm)	Power (kW)	Weight (KG)
Forcar		Worktop Freezer with 2 doors, backsplash, and cooling unit Lower compartment GN 1/1 compatible, ventilation cooling, digital controls, door access, stainless steel design (AISI 304), rounded interior, 60 mm thick thermal insulation (CFC/HCFC free), magnetic door sealing rubbers, automatic defrosting and condensate evaporation. Basic accessories: 1pc GN 1/1 sintered grid shelf and pair of rails / door. Cooling range: -22/-18°C Energy classification: B Max ambient temperature/humidity: +32°C / 55% Refrigerant: R600a	G-GN2200BT	230	1360x700x860	0,47	116
La Monferrina		Automatic crepe machine, 195 mm (7.6") round 300 pieces/hour yield of round crepes with a diameter of 195 mm, 800 mm long conveyor belt, 3-liter batter tank, digital controls, stainless steel casing, counter top design, adjustable legs, emergency stop button. The crepe size cannot be changed. Only one side of the crepe is cooked (two-sided cooking is not technologically justified). Video link in the detailed description.	C1 Round	230	420x1000x490	3,3	40
Inoxid		Work table with 2 lower shelves, backsplash Stainless steel design, 40 mm thick vibration-free worktop, 100x20 mm backsplash, adjustable legs.			1200x400		
RM Gastro	117 110 098 	Electric fry-top smooth griddle plate on open cabinet Stainless steel frame, 12 mm thick smooth cast iron cooking surface, grease collection drawer, 2 independent heating zones Cooking area: 770x560 mm Anti-splash on 3 sides, open storage underneath, on adjustable legs, Temperature range control 50-300°C,	FTH-780 E	400	800x730x900	9,0	98,5
RM Gastro	117 090 068 	Electric fryer, standing, two wells 2*17 liters, with oil drain tap Cold zone design, Temperature range control 50-190°C. With safety thermostat, safety microswitch Storage cabinet with doors, oil drain tank Basket size: 280x300x120 mm (408001104)	FE-780/17 E	400	800x730x900	27	90
RM Gastro	117 220 044 	Worktop with drawer and cabinet 2*GN with drawer 1/1-150 Work surface size: 650x530 mm, stainless steel design, with open storage underneath optional: cabinet doors	PP-780		800x730x900		65
RM Gastro	117 260 061 	Electric cooktop with 2 round burners, 2 22 cm round cooking zones, Power: 2x2.6 kW, Without oven, panel covering on 3 sides	SP-740 E	400	400x730x900	5,2	41
Stefinox		Knee operated standing hand washing station with push button and cabinet Deep-drawn basin, built-in support bracket for easy installation, upper opening d. 22 mm, adjustable legs, accessories: spout, plastic drain valve with plug, white plastic pipe siphon, material: stainless steel, 7-8 second timer, Country of origin: Italy	IPA79 IPA79		500x500x850		
UNOX		Ultra-tall open rack with tray rails (For models XEVC-0511-EPR/XEVC-0511-GPR/XEVC-0511-E1R) 7xGN1/1 tray capacity rail distance: 60 mm	XWVRC-0711-UH		732x641x888		23

Mnfr.	Image	Description	Model	Voltage (V)	Size (mm)	Power (kW)	Weight (KG)
UNOX		<p>UNOX Cheftop 'ONE' 5x GN1/1 INTELLIGENT COMBI OVEN MODEL SPECIFICS: LEFT HINGE DOOR MIND.Maps® visual technology draws cooking processes directly on the display! With MIND.Maps® you can keep track of all the cooking processes, can convert Hot air mixing cooking mode from 30C°-260C°. Humidified cooking mode from 35°C to 260°C. Hot air mixing with automatic direction change, DRY.Maxi and STEAM.Maxi control the humidity inside the oven, Rotor.KLEAN automatic cleaning system and Det&RINSE detergent Delta T cooking core thermometer, MULTI. Point core thermometer (measures at 1 point), SOUS-VIDE core thermometer PROGRAMS: you can store 256 user programs, with names and pictures. AIR.Maxi technology: 4 programmable, alternating air speeds, + 4 semi-static cookers mode, STEAM.Maxi technology: humidification 35°C – 130°C STEAM.Maxi technology: combination of wet and dry air 35C – 260C</p>	XEVC-0511-E1LM	400	750x783x675	9,3	66
RM Gastro	101 600 530 	<p>Hot Dog Roller Grill Stainless steel, 8 (32 cm) rotating oven cylinders with heating elements Temperature control between 30-90°C</p>	CW 8	230	460x350x200	1,8	13
Inoxid		<p>Wall canopy hood Stainless steel panels, removable and dishwasher safe grease filter. Includes lighting fixtures, grease collection trough, grease drain tap, double side walls. Air permeability of grease traps depending on air speed: 420-500 m³/hour/insert. The price does not include the cost of the exhaust motor and related air ducts. Pipe stub: optional Material: KO33, AISI304</p>	FD120/4000	230	4000x1200x450		
Inoxid		<p>Work table with two lower shelves, back-splash Anti-vibration worktop, back-splash: 100 x 15 mm, 40 mm thick anti-vibration worktop, adjustable legs, stainless steel design,</p>	MA2PHF 70-70	230	700x700x900		
Forcar		<p>Sandwich/Salad Prep Table with Three Door Refrigerated Base Lower compartment GN 1/1 compatible, topping holder GN 1/6 (8pcs) compatible. Static cooling, digital controls, 3 opening doors, topping cooler with opening lid (removable). Stainless steel version (AISI 304), 40 mm thick thermal insulation (CFC/HCFC free), magnetic door sealing rubbers, rounded interior, central evaporator, automatic defrosting and condensation evaporation. Basic accessories: 2 GN 1/1 grid shelves. Options: left-hand unit, wheel set, etc... Cooling range: +2/+8°C Max ambient temperature/humidity: +32°C / 55% Refrigerant: R600</p>	G-PS300	230	1370x700x1010	0,23	161
Uniscool		<p>Heated display case, tall design, GN 2/1 Designed to be placed on or recessed into the counter, stainless steel-glass design (AISI 304), ventilation heating, water tray for humidification, electromechanical control, LED lighting, 1-1-1 pc 448/398/338 mm deep wire shelves, doors open on service side, adjustable feet, single pane glass. Heating range: +30/+90 °C Nominal consumption: 33.6 kW/day</p>	Thaya HOT GN2 High 119T10V20d	230	746x718x854	2,1	91

Mnfr.	Image	Description	Model	Voltage (V)	Size (mm)	Power (kW)	Weight (KG)
Inoxid		Sneeze Guard Square design with flat safety glass, stainless steel brackets. Fixed to container frame.			1300×300		
Uniscool		Refrigerated display case, tall design, GN 2/1 internal size Designed to be placed on or recessed into the counter, stainless steel-glass design (AISI 304), ventilation cooling, digital control, LED lighting, 1-1-1 448/398/338 mm deep interior wire shelves, doors open on service side, automatic defrost, air-cooled unit, adjustable feet, single pane glass (condensation may occur in case of high humidity on surface). Cooling range: +2/+6 °C Ambient temperature/humidity maximum: +25°C / 60% Refrigerant: R455a Nominal consumption: 5.96 kW/day	Thaya COLD GN2 High 119T00V20d	230	746×718×854	0,46	113
Inoxid		Appliance counter for 2 Uniscool display cases 2 shelves, kick plate, covered on three sides and open front, short legs with adjustable bases and covers, stainless steel design.			1500×700×667	40	
Inoxid		Appliance counter for 1 Uniscool display case 2 shelves, kick plate, covered on three sides and open front, short legs with adjustable bases and covers, stainless steel design.			750×700×667	25	
Cola		Beverage Cooler DISTRIBUTER PROCUREMENT			600×600×850	0,2	
Beer		Tap kegerator draft beer dispenser, beer tap tower, tray with sprayer to rinse glasses. DISTRIBUTER PROCUREMENT				0,5	
Inoxid		Service table prepped for drink coolers and a beer tap Vibration-free worktop, 100 mm high left side splash guard, stainless steel design (AISI 304), adjustable legs reinforced on three sides.			3200×700×900		
Inoxid		Coffee-maker station, with drawer, prepped for beverage cooler Waste drawer, vibration-free worktop, 100 mm high right side splash guard, stainless steel design (AISI 304), adjustable legs reinforced on three sides.			800×700×1100		
Coffee		Coffee maker DISTRIBUTER PROCUREMENT				3	
Coffee		Coffee grinder DISTRIBUTER PROCUREMENT				1	
Inoxid		Service table, prepped for beverage coolers Anti-vibration worktop, stainless steel design (AISI 304), adjustable legs reinforced on three sides			1400×700×900		



Continest IP: Patent Application WO 2019 – 064036, Trademark: WIPO 227509



Our sales and engineering team are at your service

No request is too big; no question is too trivial. Communication is key! Reach out to us today and get started on a journey that will change your business and your life.

[CONTACT US →](#)